

tesa®

Product Information



55533

Product Features

- Water resistant anti slip tape: ideal for bathtubs, showers, tubs, stairs and other slippery surfaces
- Strong acrylic adhesive resists cracking and peeling
- Easy to apply- simply cut to the needed size with scissors
- Temperature resistant up to 50° C
- UV resistant
- Resistant to cleaning agents
- Tested according to DIN 51097
- 5m x 25mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Type of adhesive acrylic

Properties/Performance Values

- | | | | |
|------------------------|---------------|-------------------------------|--|
| • Abrasion resistance | yes | • Suitable surfaces | Tiles, Most plastics, Plaster, Steel, Stone, Metal |
| • Adhesive strength | High adhesion | | |
| • Residue free removal | no | | |
| • Solvent free | yes | • Temperature resistance | yes |
| | | • Temperature resistance max. | 50 °C |
| | | • Temperature resistance min. | 0 °C |

tesa®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=55533DIY>