

tesa® Professional

Product Information

60022

Product Features

- Suitable for heavy weight materials with rough and uneven surfaces
- Film forming spray
- Spray direction can be set either horizontal or vertical
- Adjustable spray quantity (H: high, M: medium, L: low)
- Resistant to damp and temperature from -30°C up to +80°C (short term even 100°C)
- Free from silicone

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- Silicone free yes

Properties/Performance Values

• Adhesive strength	High adhesion	• Suitable for children of 3 years of age	no
• Chemical resistance	yes	• Suitable surfaces	Even wood, Stone, Brick, Acrylic glass
• Compostable	no		
• Hazard material	yes	• Temperature resistance	yes
• Humidity resistance	yes	• Temperature resistance max.	80 °C
• Recommended distance of spraying	30 cm	• Temperature resistance min.	-30 °C
• Residue free removal	no	• UV resistant	yes
• Solvent free	no	• Washable	no
		• Waterproof	yes

tesa® Professional

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=60022>