

tesa® Powerstrips

Product Information

58813

Product Features

- Ideal to hang up decorative objects for seasonal or special occasions (e.g. Easter, Christmas, birthdays, wedding, etc.) in multiple ways
- Secure hold for medium weight (1 kg) decorations on a variety of surfaces*
- Removable without trace thanks to the Powerstrips® technology
- Limited UV-resistance Deco Hooks reusable with new tesa Powerstrips® transparent Large

1

¹ *Not suitable for use on styrofoam, foamed material, surfaces with non-sticking coating, porous materials

Application Fields

- How to apply - Step by step
1. Clean the surface with alcohol or silicone-free glass cleaner
 2. Apply the Powerstrip® Transparent strip on the surface - press for 5 seconds minimum
 3. Stick the hook onto the strip - press for 5 seconds minimum
 4. Make sure the tab can be accessed for removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|-----------------------|------------------|-----------------|-------------|
| • Type of adhesive | synthetic rubber | • Hook shape | Rectangular |
| • Holding power up to | 1 Kg | • Silicone free | yes |

Properties/Performance Values

- | | | | |
|--------------------------------|---|--------------------------|-----|
| • Application temperature from | -15 °C | • Ozone resistance | yes |
| • Applicationfield | Kitchen, Living room,
Children's room,
Office, Hall, Bathroom | • Residue free removal | yes |
| | | • Reusable | yes |
| • Chemical resistance | no | • Solvent free | yes |
| • Hazard material | no | • Temperature resistance | yes |
| • Humidity resistance | no | • UV resistant | yes |
| • Material | PS (polystyrene) | • Waterproof | no |
| • Oil and grease resistance | no | | |



tesa® Powerstrips

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=58813>