

tesa®

Product Information



77762

Product Features

- For smooth and solid surfaces like tiles indoors
- For objects up to 2kg per nail or 4kg using 2 nails
- Removable without a trace
- Reusable with a new strip

Application Fields

How to apply – Step by step1. To ensure the closest, strongest possible bond, clean the surface with a silicone-free window cleaner or methylated spirit. The surface should be completely dry before application.

2. The Adhesive Strip should be applied first to the rougher surface.

3. Press down evenly over the entire strip for at least 5 seconds and then remove the protective foil. Be careful not to touch the exposed adhesive area at any time.

4. Now apply your tesa® Adhesive Nail by aligning it with the top edge of the strip and then folding it down. Press down evenly over the entire nail for at least 5 seconds.

5. The tab should be left accessible behind your object or beneath the nail for easy removal.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Type of adhesive	synthetic rubber	• Holding power of strip up to	2 Kg
--------------------	------------------	--------------------------------	------

Properties/Performance Values

• Application temperature from	-15 °C	• Ozone resistance	no
• Chemical resistance	no	• Residue free removal	yes
• Hazard material	no	• Reusable	yes
• Humidity resistance	no	• UV resistant	no
• Material	PS (polystyrene)	• Waterproof	no
• Oil and grease resistance	no		

tesa®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=77762>