

tesa® Powerstrips

Product Information

57533, 58275, 57519, 57543

Product Features

- Easy to mount without drilling, screws or nails
- Strong hold up to 1kg
- Removable without trace thanks to the Powerstrips technology
- Made from high quality plastic
- Usable on tiles, glass, wood, plastic and a variety of other surfaces*
- Hooks reusable with tesa Powerstrips SMALL
- Completely covered tesa Powerstrip

*Not suitable for use on styrofoam, foamed material, surfaces with non-stick coating, porous materials

Application Fields

How to apply - Step by step:
1. Clean the surface with alcohol or silicone-free glass cleaner
2. Apply the Powerstrip® Small strip on the surface - press for 5 seconds minimum
3. Open the hook and stick the back of the hook onto the strip - press for 5 seconds minimum
4. Close and snap-lock the hook.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Type of adhesive	synthetic rubber	• Hook shape	Oval
• Holding power up to	1 Kg		

Properties/Performance Values

• Application temperature from	15 °C	• Oil and grease resistance	no
• Application temperature to	35 °C	• Ozone resistance	no
• Application field	Bathroom, Kitchen	• Residue free removal	yes
• Chemical resistance	no	• Reusable	yes
• Hazard material	no	• Reusable with	Powerstrips Small
• Humidity resistance	no	• Solvent free	yes
• Material	PS (polystyrene)	• Temperature resistance	yes
• Number of hooks	Single	• UV resistant	no

tesa® Powerstrips

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=57533>