

# tesamoll®

## Product Information

5389, 5393, 55706

### Product Features

- Saves up to 40% of energy costs
- Self-adhesive, long-lasting rubber D-Profile
- Seals all gaps from 3 to 7mm
- Durability: 8 years
- Weather-, UV- and ozone-resistant
- Wipe-clean
- Easy to apply and to fit without screws or nails
- Easy to remove
- Temperature-resistant from -50°C to +60°C

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

• Backing material	EPDM rubber foam	• Energy saving potential up to	40 %
• Type of adhesive	synthetic rubber	• Gap coverage up to	7 mm

### Properties/Performance Values

• Chemical resistance	no	• Solvent free	yes
• Durability	8 years	• Temperature resistance	yes
• Humidity resistance	yes	• Temperature resistance max.	60 °C
• Material	Fabric, Synthetic	• Temperature resistance min.	-20 °C
• Residue free removal	no		

# tesamoll®

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=5393>