

tesa®

Product Information

55587, 51074, 55588, 55629, 55589, 51073

Product Features

- Extremely strong and durable tape
- Very strong adhesion
- Hand-tearable
- Resistant to water, temperature, UV and cleaning agents

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Properties/Performance Values

• Abrasion resistance	yes	• Suitable surfaces	Tiles, Most plastics,
• Adhesive strength	High adhesion		Plaster, Steel, Stone,
• Hand tearability	yes		Metal
• Residue free removal	no	• Temperature resistance	yes
• Solvent free	yes	• Temperature resistance max.	50 °C
		• Temperature resistance min.	0 °C

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=55588DIY>