



tesa® Loxx bathroom wall hook, chromed metal, self-adhesive



Product Information

BNR 40277

Product Description

The self-adhesive tesa® Loxx bathroom wall hook is easily and reliably wall-mounted. Without drilling, there's no damage to walls or tiles. Removal of the hook is possible at any time and doesn't leave a trace behind. It can be relocated with a new adapter BK20. The rounded, spirited design fits any bathroom décor.

Product Features

- Bathroom wall hook, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- High gloss chrome-plated metal, round style, circular wall plate, sprightly design
- Reliable hold, waterproof, guaranteed stainless
- Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Simple to remove without a trace, conveniently reusable with adapter BK20
- Effortless to attach without drilling
- Product dimensions: 55mm x 50mm x 68mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|-----------------------|-------------------------|--------------|-------|
| • Type of adhesive | Silane modified polymer | • Hook shape | Round |
| • Holding power up to | 6 Kg | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------------|------------------------|-------|
| • Chemical resistance | no | • Residue free removal | yes |
| • Design series | tesa® LOXX | • Reusable | yes |
| • Humidity resistance | yes | • Shape of wall piece | Round |
| • Material | Chromed metal | • Solvent free | yes |
| • Number of hooks | Single | • UV-resistant | yes |



tesa[®] Loxx bathroom wall hook, chromed metal, self-adhesive

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?cp=40277>