

# tesa® Loxx bath hook, chromed metal, self-adhesive

### **Product Information**

BNR 40276

### **Product Description**

It's a breeze to attach the self-adhesive tesa® Loxx bath hook to a wall without drilling and without damage to walls or tiles. The bath hook can also easily be removed at your convenience, without a trace. Reuse only requires a new adapter BK22. The hook's spirited, rounded design is a pleasure to see.

#### **Product Features**

- Bath hook, with tesa® Power.Kit technology (all-in-one adhesive mounting solution)
- High gloss chrome-plated metal, round style, circular wall plate, cheerful design
- Reliable hold, waterproof, guaranteed stainless
- · Works on tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- · Does not work on wallpaper, stucco and other surfaces with non-stick coating
- Fast to remove without a trace, reusable with adapter BK22
- · Easy to apply without drilling
- Product dimensions: 42mm x 42mm x 50mm

#### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Applications**

•	Type of adhesive	Silane modified	•	Hook shape	Round
		polymer			
•	Holding power up to	6 Kg			

#### **Properties/Performance Values**

•	Chemical resistance	no	•	Residue free removal	yes
•	Design series	tesa® LOXX	•	Reusable	yes
•	Humidity resistance	yes	•	Shape of wall piece	Round
•	Material	Chromed metal	•	Solvent free	yes
•	Number of hooks	Single	•	UV-resistant	yes



# tesa® Loxx bath hook, chromed metal, self-adhesive

**Product Information** 

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.