



# tesa® 4761

## Product Information



Polyurethane open cell single sided foam tape 3mm thick (grey & white)

### Product Description

tesa 4761 is a 3mm thick polyurethane open cell foam tape with an acrylic adhesive on one side. The open cell foam makes it suitable for sealing from dust and draft, while the acrylic adhesive allows for easy application to various surface materials. tesa 476 Series foam tape is soft and highly conformable, and suitable for use on uneven surfaces. The polyurethane foam also helps to absorb sound and dampen vibrations. tesa 476 Series is available in 3mm, 6mm, 9mm and 12mm thicknesses, and in grey and white colours.

### Applications

tesa 476 Series foam tape is a cost effective solution for a variety of sealing applications in the concreting and general industrial market.

Application ideas:

- Dam wall sealing (concreting)
- Draught and dust sealing on doors and windows
- Sealing concrete form work
- Sealing and noise dampening between office partitions and walls or ceilings
- Vibration dampening in appliances
- Dust and insect filter on lights

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Applications

- |                    |               |                   |         |
|--------------------|---------------|-------------------|---------|
| • Backing          | PU foam, soft | • Total thickness | 3000 µm |
| • Type of adhesive | acrylic       |                   |         |

### Properties/Performance Values

- |                       |       |                               |        |
|-----------------------|-------|-------------------------------|--------|
| • Elongation at break | 100 % | • Suitable for die cutting    | yes    |
| • Chemical Resistance | low   | • Temperature resistance max. | 80 °C  |
| • Compression Set     | 10 %  | • Temperature resistance min. | -10 °C |
| • Flame retardance    | low   | • Water resistance            | low    |

### Adhesion to Values

- |         |         |
|---------|---------|
| • Steel | 24 N/cm |
|---------|---------|



# tesa® 4761

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04761>