

tesa® 52450

Product Information



High Strength Kraft Flat Back Paper Tape

Product Description

High Strength Kraft Flat Back Paper Tape, hand tearable, good resistance to moisture. Very low elongation at breaking point. High adhesion. Good quick stick

Application Fields

- Carton sealing tape
- Splicing of paper and plastic films
- Light strapping and bundling

Packaging and carton sealing for medium and heavy weight cartons. Splicing of paper, corrugated board and plastic films. Light strapping, bundling and unitising. Light duty sand blasting.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing | flat paper | • Total thickness | 210 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|-------|--------------------|----------|
| • Elongation at break | 2.5 % | • Tensile strength | 6.1 N/cm |
|-----------------------|-------|--------------------|----------|

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 7.5 N/cm |
|---------|----------|

tesa® 52450

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=52450PV0WT>