



tesa® 53128 PV18

Product Information

Mid Grade 100°C Yellow Masking

Product Description

tesa® 53128 PV18 is a thin and flexible standard grade masking tape with a yellow coloured crepe paper backing and a natural rubber adhesive. The masking tape is suitable for a wide range of general masking applications without or with subsequent oven-drying up to a temperature of 80°C/1h (Short term: 100°C / 30 minutes). It can be also used in indoor painting applications up to 7 days.

The natural rubber adhesive provides a good adhesion to multiple surfaces, like metal, rubber, glass and plastic. The fine crepe paper backing is flexible and conformable and is easy to tear by hand. Paints and fillers adhere well to the reverse side, preventing any kind of flaking.

Features & Benefits:

- Tear resistant backing provides demasking in one piece
- Excellent adherence of paints and fillers
- Good peel adhesion provides secure bond on different substrates
- Residue free removal up to 7 days indoor
- Temperature resistance up to 80°C /1 h and 100°C / 0,5h
- Consistent tesa Quality

Application Fields

- tesa® 53128 PV18 is a flexible masking tape used for spray-painting, painting, and varnishing applications
- The masking tape has good holding power on various surfaces
- The tape is suitable for oven-drying with temperatures of up to 80°C/1h and 100°C/0,5h.
- Indoor painting (one week clean removal)

For latest information on this product please visit <http://l.tesa.com/?ip=53128>



tesa[®] 53128 PV18

Product Information

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing	slightly-creped paper	• Total thickness	120 µm
• Type of adhesive	natural rubber		

Properties/Performance Values

• Elongation at break	9 %	• Easy to remove	yes
• Tensile strength	32 N/cm	• Hand tearability	very good

Adhesion to Values

• Steel	3 N/cm
---------	--------

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=53128>