

tesa® 51482

Product Information



HD PVC Pipe Wrap, Isolation tape

Product Description

Highly flexible anti corrosive tape, Excellent insulating properties.

Applications

- · Electrolysis barrier between dissimilar metals
- · Joining sub concrete membranes

For the corrosion and abrasion protection of undergournd and above ground pipes. For the joining of large electrical cables and conduit. For use as an electrolysis barrier between dissimilar metals. For joining subconcrete membranes.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

| • | Backing | PVC film | • | Total thickness | 250 μm |
|---|------------------|--------------|---|-----------------|--------|
| • | Type of adhesive | rubber based | • | Color | black |

Properties/Performance Values

| | • | Elongation at break | 230 % | Tensile strength | 42.4 N/cm |
|--|---|---------------------|-------|--------------------------------------|-----------|
|--|---|---------------------|-------|--------------------------------------|-----------|

Adhesion to Values

• Steel 2.2 N/cm



tesa® 51482

Product Information

Additional Information

Highly flexible anti-corrosive tape. Puncture resistant P.V.C backing. Excellent insulation properties.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

