



tesa[®] 60985

Product Information

High Performance Double Sided Tissue Tape

Product Description

tesa[®] 60985 is a high performance double sided tissue tape coated on both sides with aggressive acrylic adhesive. The thin & flexible construction allows it to conform to irregular surfaces, while the high quality adhesive ensures it adheres securely to many hard to stick surfaces. High temperature resistance of up to 150°C short term makes it suitable in a wide range of applications. Translucent colour.

Applications

- Foam and fabric lamination
- Window curtain and blind assembly
- Mounting metallic and plastic nameplates and control panels
- Mounting small signs
- Bonding to low surface energy (hard to stick) materials

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|---------|-------------------|-------------|
| • Backing | Paper | • Total thickness | 170 µm |
| • Type of adhesive | acrylic | • Color | translucent |

Properties/Performance Values

- | | | | |
|-----------------------|-----|--------------------|----------|
| • Elongation at break | 3 % | • Tensile strength | 9.6 N/cm |
|-----------------------|-----|--------------------|----------|

Adhesion to Values

- | | |
|-------------------|----------|
| • Steel (initial) | 7.5 N/cm |
|-------------------|----------|



tesa[®] 60985

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60985>