



tesa® 50537

Product Information



Temporary fixation tape for use on glass surfaces

Product Description

tesa® 50537 consists of a very robust synthetic fleece material coated with a synthetic elastomer adhesive. The adhesive is designed for reliable adhesion to glass surfaces assuring traceless removability, even for long-term outdoor use.

Product Features

- Thick and robust fleece material
- Can be fixed by sewing to all sorts of material
- Reliable adhesion to glass with traceless removal
- UV resistant for outdoor use
- Suitable for die cutting

Applications

tesa® 50537 is especially suitable for mounting automotive semi hoods for surface protection during transport.

Example applications are:

- Fixation of covers on windshields

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|-----------|--------|-------------------|--------|
| • Backing | fleece | • Total thickness | 170 µm |
|-----------|--------|-------------------|--------|

Properties/Performance Values

- | | | | |
|-----------------------|------|----------------------------|-----|
| • Chemical Resistance | good | • Suitable for die cutting | yes |
| • Easy to remove | yes | | |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 2.5 N/cm |
|---------|----------|



tesa[®] 50537

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50537>