



tesa[®] 4613 Utility Duct Tape

Product Information

Utility grade duct tape



Product Description

tesa[®] 4613 is a utility-grade duct tape. It consists of a 27-mesh woven PET/cotton fabric backing, coated with a natural rubber adhesive. tesa[®] 4613 duct tape is a flexible, hand-tearable self-adhesive tape. The duct tape can be used for a wide range of applications, such as marking, fastening, sealing and packaging. tesa[®] 4613 features excellent adhesion even on rough surfaces. It is water-repellent and can easily be torn by hand. The tape's natural rubber adhesive system features excellent adhesion to multiple surfaces, both polar and non-polar as well as a high tack and short dwell time to reach final adhesion level. Additionally, the duct tape's mesh backing makes it resistant to temperatures of up to 95°C for as long as 30 minutes at a time.

Product Features

- It comprises a natural-rubber adhesive mass and can be torn by hand.
- The duct tape is also suited to rough surfaces and is waterproof.

Applications

- tesa[®] 4613 is suitable for indoor and outdoor applications - even on rough surfaces
- The high-quality fabric tape can be used for securing covering materials, for sealing cardboard or for making pipes waterproof
- The duct tape can be used to fasten protective films or seal ducts
- Furthermore, the duct seal is used for fixing, marking and packing
- The tape should not be used on painted surfaces

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|--------------------|-------------------|--------|
| • Backing | PE laminated cloth | • Total thickness | 180 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|--------------------------|---------|-------------------------------------|--------------------------|
| • Elongation at break | 18 % | • Hand tearability | good |
| • Tensile strength | 30 N/cm | • Humidity resistance | good |
| • Ageing resistance (UV) | good | • Mesh | 27 count per square inch |
| • Fluorescent | no | | |
| • Fogging | low | • Temperature resistance short term | 80 °C |

For latest information on this product please visit <http://l.tesa.com/?ip=04613>



tesa[®] 4613 Utility Duct Tape

Product Information

Adhesion to Values

- Steel 4.3 N/cm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04613>