



tesa® 4308

Product Information



Premium Masking Tape for Demanding Masking Applications

Product Description

tesa® 4308 is a smooth crepe paper masking tape with a natural-rubber adhesive, which has been developed especially for highly demanding masking applications in the automotive aftermarket and transportation industries. The automotive adhesive tape is suitable for masking during spray painting with subsequent oven drying, resisting temperatures up to 110°C. tesa® 4308 can be used either with 2-component or water-based paints. The backing resists bleed-through of paint and is highly conformable and flexible. The masking tape features excellent adhesive properties on different substrates, such as metal, rubber, glass and plastic as well as high tack and good quick adhesion. tesa® 4308 can be removed easily without leaving any residue and leaves clean paint results with good paint edges.

Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

Application Fields

- tesa® 4308 has been developed specifically for demanding masking applications in the car body repair and transportation industry
- The masking tape's flexible backing allows good conformability to irregular surfaces
- The automotive tape is suitable for spray painting with subsequent oven drying, resisting temperatures of up to 110°C
- tesa® 4308 features hand-tearability and residue-free removal

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|-----------------------|--|--------|
| • Backing | slightly-creped paper | • Total sustainable product excl. liners by weight (acc. EN 16785) | 50 % |
| • Type of adhesive | natural rubber | • Total thickness | 170 µm |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 13 % | • Hand tearability | very good |
| • Tensile strength | 53 N/cm | • Paint anchorage | very good |
| • Conformability | good | • Sharp color edge | very good |
| • Easy to remove | yes | • Temperature resistance (60 min) | 100 °C |

For latest information on this product please visit <http://l.tesa.com/?ip=04308>



tesa® 4308

Product Information

Adhesion to Values

- Steel 4 N/cm

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04308>