



tesa® 64283 PV1 Easy Unwinding



Product Information

Tensilised non-staining strapping tape

Product Description

tesa® 64283 PV1 is a tensilised polypropylene strapping tape with a natural rubber adhesive system.

tesa® 64283 PV1 is specially designed for safe fixation of goods during all types of transports. The product ensures excellent removability, even from very critical substrates.

The specially-treated backing allows easy handling both manually and with dispenser. Due to its high conformability tesa® 64283 PV1 exhibits a flexible adaption to 3-D shaped surfaces.

Application Fields

Closing, holding, securing and surface protection of components in various industries.

- “L” and “C” clipping
- Special transport securing in the Appliance and Office Automation Industry

Because of the easy unwinding feature, tesa®64283 PV1 is especially recommended when automatic dispenser is in use.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|-------|
| • Backing | MOPP | • Total thickness | 77 µm |
| • Type of adhesive | natural rubber | • Color | blue |

Properties/Performance Values

- | | | | |
|-----------------------|----------|-----------------------------|----|
| • Elongation at break | 35 % | • No discoloration | no |
| • Tensile strength | 185 N/cm | • Residue-free removability | no |

Adhesion to Values

- | | |
|---------|----------|
| • Steel | 4.3 N/cm |
|---------|----------|



tesa® 64283

PV1 Easy Unwinding

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64283>