



# tesa<sup>®</sup> 4262

## A

### Product Information

General purpose polypropylene carton sealing tape with an acrylic adhesive

### Product Description

tesa<sup>®</sup> 4262A is a general purpose polypropylene carton sealing tape. Suitable for use on recycled board and under shrink wrap. Operating temperature between -50°C and 100°C.

The well balanced tack and high shear resistance of the adhesive secures a good sealing immediately after application.

### Product Features

- Suitable for use on recycled board and under shrink wrap.
- The well balanced tack and high shear resistance of the adhesive secures a good sealing immediately after application.

### Applications

- Packaging, bundling and closing
- Carton sealing for light to medium cartons
- It can be used on all common hand dispensers and machines
- Colors available are transparent and brown

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Applications

- |                    |         |                   |       |
|--------------------|---------|-------------------|-------|
| • Backing          | BOPP    | • Total thickness | 52 µm |
| • Type of adhesive | acrylic |                   |       |

### Properties/Performance Values

- |                       |         |                         |     |
|-----------------------|---------|-------------------------|-----|
| • Elongation at break | 180 %   | • Automatic application | yes |
| • Tensile strength    | 45 N/cm | • Manual application    | yes |

### Adhesion to Values

- |         |          |
|---------|----------|
| • Steel | 2.1 N/cm |
|---------|----------|



# tesa<sup>®</sup> 4262

# A

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04262>