

tesa® 4104 coloured

Product Information

Brilliant coloured filmic packaging tape

Product Description

tesa® 4104 is a premium packaging tape based on a polyvinyl chloride (PVC) film backing and a natural rubber adhesive. It performs exceptionally on a variety of different surfaces, including various kinds of cardboards and plastic boxes or bags, always ensuring a safe closure. The PVC backing offers excellent resistance against weathering as well as chemicals and fire. The natural rubber adhesive system is designed for best results in applications on either polar or non-polar surfaces. The large variety of highly visible colours also makes tesa® 4104 ideal for masking or colour-coding. tesa® 4104 is easily printable and is available as a transparent version and in seven different colours: black, white, red, orange, yellow, blue and green.

Application Fields

- · Ideal for sealing small boxes, both cardboard and plastic
- · Can also be used for safe and easy sealing of tins and plastic bags
- Offers excellent adhesion to various different surfaces
- The large variety of available colours makes tesa® 4104 ideal for marking and colour-coding
- tesa® 4104 in red enables sharp-edge masking for multicolour painting

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- Backing PVC film - Total thickness 67 μm

Type of adhesive natural rubber

Product Assortment

Available colors transparent

Properties/Performance Values

Elongation at break
Tensile strength
60 %
Low noise unwinding
Printability
yes

Automatic application no

Adhesion to Values

• Steel 2.3 N/cm



tesa® 4104 coloured

Product Information

Additional Information

tesa® 4104 is easily printable. Available colours: black, white, red, orange, yellow, blue and green.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

