

tesa® 4260

Product Information



General Purpose Polypropylene Carton Sealing Tape with an Acrylic Adhesive

Product Description

tesa® 4260A is a polypropylene-based packaging tape with an acrylic adhesive, used for general carton sealing and packaging applications. The packing tape is available in hand rolls and machine rolls and can be used manually or with an automatic dispenser. It is ideal for application in high volumes on light- to medium-weight cartons. tesa® 4260 is suitable for use on recycled board and under shrink wrap. The acrylic adhesive features a strong hold on easy to adhere surfaces (high surface energy / polar substrates), as well resistance to solvents and ageing stability.

Application Fields

- High volume, packaging and carton sealing for light- to medium-weight cartons.
- Suitable for application on recycled board and under shrink wrap.
- Can be used manually or with a carton sealing machine.
- The packaging tape is available in a transparent or brown version.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 45 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------|-----|
| • Elongation at break | 100 % | • Automatic application | yes |
| • Tensile strength | 42 N/cm | • Manual application | yes |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 3 N/cm |
|---------|--------|

tesa® 4260

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4260PV2>