



# tesa® 54337 PV1



## Product Information

Precision die cuts for hole covering applications

## Product Description

tesa® 54337 die cuts consist of a high quality PVC film coated with an acrylic adhesive. Die cuts are supplied on a white glassine liner.

Features:

- Perfect optical appearance
- Reliable adhesion on painted surfaces
- Good sealing properties against moisture, water and dust
- Temperature-resistant up to 110 °C
- Good mechanical properties with respect to abrasion and puncture resistance
- Good water resistance

## Application Fields

tesa® 54337 die cuts are suitable for permanent hole covering solutions. This high performance PVC tape provides a perfect design and good acoustic properties.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                   |                   |        |
|--------------------|-------------------|-------------------|--------|
| • Backing          | PVC film          | • Total thickness | 450 µm |
| • Type of adhesive | tackified acrylic | • Color           | black  |
| • Type of liner    | glassine          | • Color of liner  | white  |

## Properties/Performance Values

- |                       |          |                                   |           |
|-----------------------|----------|-----------------------------------|-----------|
| • Elongation at break | 289 %    | • Chemical Resistance             | very good |
| • Tensile strength    | 109 N/cm | • Suitable for die cutting        | yes       |
| • Abrasion resistance | good     | • Temperature resistance (30 min) | 110 °C    |

## Adhesion to Values

- |                   |          |
|-------------------|----------|
| • Steel (initial) | 6.9 N/cm |
|-------------------|----------|



# tesa® 54337 PV1

## Product Information

### Additional Information

tesa® 54337 is available upon request in customer specific dimensions and can be delivered according to customer requirements and applications in either roll form or as sheets.

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=54337>