



tesapack® 6300 Hand Dispenser Economy

Product Information

Dispenser ECONOMY for packaging tapes

Product Description

The tesa® 6300 hand dispenser is a cost effective dispenser for the professional sealing of all kinds of tesa® packaging tape in packaging and production applications. The dispenser has tension control, to allow tesa® packaging tapes to be easily unwound and applied without difficulty. The blade is covered with a top to prevent injuries. To use the dispenser, place it on the carton and pull it towards yourself. The contact roller presses the tape down firmly as it is applied from the roll. The tape is then cut by the serrated blade by tilting the dispenser. The cut end of the tape is pressed onto the carton by the flexible application plate.

Product Features

- The dispenser has a tension control so that even easy unwinding tesa® tapes can be used without difficulty.
- The blade is covered with a top to prevent injuries.

Applications

- The tesa® 6300 hand dispenser is used for professional sealing and packaging
- Adjustable tension control ensures easy application

Properties/Performance Values

• Adhesive strength	_NULL	• Roll width max	55 mm
• Applicationfield	Home, Office	• Serrated blade	no
• Batteries included	no	• Solvent free	yes
• Batteries required	no	• Spare part service	no
• Low noise unwinding	_NULL	• Suitable surfaces	_NULL
• Material	Metal	• Tear resistance	_NULL
• Max roll length	66 m	• Tension control	yes
• Max. core diameter	3	• Transparency	_NULL
• Reusable	yes	• Writable	no



tesapack[®] 6300

Hand Dispenser Economy

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=06300>