



tesa® 52330

Product Information



Plate mounting in flexographic printing, especially corrugated board postprint

Product Description

tesa® 52330 is especially well suited to plate mounting in corrugated board postprint, due to its ideal adhesive characteristics and optimal backing properties.

Adhesive properties

- *High adhesive coating weight to ensure the secure mounting of plates that have been "back ground"
- *The adhesive properties also allow secure vertical storage of mounted plates

Backing properties

- *tesa® 52330 is very flexible, yet stable, due to its fabric backing material and therefore are ideally suited for plates in corrugated board postprint
- *The stability of the backing also ensures that mounted plates can be stored vertically

Additional properties

- tesa® 52330 has a creped paper liner to prevent the formation of air bubbles during plate mounting

Application Fields

tesa® 52330 is especially well suited to plate mounting in corrugated board postprint, due to its ideal adhesive characteristics and optimal backing properties.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-----------------|--------------|
| • Backing | cloth | • Type of liner | creped paper |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | |
|----------------------|-----|
| • Thickness category | 380 |
|----------------------|-----|



tesa[®] 52330

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=52330>