



tesa® Sleeve 51608 PV8



Product Information

PET fleece Sleeve for enhanced flexibility

Product Description

tesa Sleeve® 51608 PV8 is a PET fleece coated at the edges with rubber based adhesive for lengthwise application.

Major Features:

- High flexibility
- Noise damping
- Easy and efficient lengthwise application

Color: Black

Application Fields

tesa Sleeve® 51608 PV8 is designed for the passenger compartment, providing high flexibility.
For lengthwise application

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Properties/Performance Values

- | | | | |
|---|---------|-------------------------------|--------|
| • Abrasion resistance (10mm mandrel, LV312) | Class A | • Temperature resistance max. | 105 °C |
| • Abrasion resistance (5mm mandrel, LV312) | Class A | • Temperature resistance min. | -40 °C |
| • Noise damping (LV312) | Class C | | |

Adhesion to Values

- Steel 3 N/cm

Additional Information

Standard widths: 80, 100, 130, 180, 250 mm
Standard lengths: 50 m

- Most combinations of width and length are possible
- Also available with customized perforation

Harness diameter / tesa Sleeve® width recommendation

< Ø 18 mm / 80 mm > Ø 18 mm – 24 mm / 100 mm

Ø 24 mm – 33 mm / 130 mm

Ø 33 mm – 49 mm / 180 mm

Ø 49 mm – 72 mm / 250 mm

For latest information on this product please visit <http://l.tesa.com/?ip=51608>



tesa[®] Sleeve 51608 PV8

Product Information

Additional Information

- Standard core diameter: 76 mm

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=51608>