




# NOPI® 4051

## Product Information



## Plasticised PVC Ducting and Joining Tape

### Product Description

NOPI® 4051 is a duct tape, comprised of a soft polyvinyl chloride (PVC) backing in combination with a rubber-based adhesive. The highly conformable backing has good impact and abrasion resistance. The tape is weatherproof and offers a good UV-stability. The rubber adhesive holds well on a wide variety of surfaces. NOPI® 4051 is available in the colors silver and black.

#### Benefits:

- Highly conformable backing with good impact and abrasion resistance
- Good adhesion to a wide variety of surfaces
- RoHS and REACH compliant
- Lead free

### Application Fields

- The tape is ideally used for joining poly-sheeting used in the building industry

\* Suitable for applications such as joining and sealing flexible air-conditioning ductwork

\* The rubber adhesive has a high adhesive strength on numerous surfaces, including those with low surface energy that are difficult to adhere to

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing          | soft PVC       | • Total thickness | 130 µm |
| • Type of adhesive | natural rubber |                   |        |

### Properties/Performance Values

- |                    |         |
|--------------------|---------|
| • Tensile strength | 25 N/cm |
|--------------------|---------|



# NOPI® 4051

## Product Information

### Additional Information

Available in the colours silver and black.

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04051>