



tesa[®] 60057 Spacer Tape

Product Information

6630µm double sided high density PU foam tape

Product Description

tesa[®] 60057 is a double sided open cell PU foam tape. The tape is equipped with an acrylic adhesive. The open cell PU foam allows an air and moisture transport through the tape, permitting an optimum silicone curing.

Applications

tesa[®] 60057 was designed as a spacer element for two- and four- sided structural glazing systems. The tape creates a gap of the correct dimensions for the silicone adhesive.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

• Backing	PU foam	• Color	black
• Type of adhesive	acrylic	• Color of liner	blue
• Type of liner	PE	• Thickness of liner	100 µm
• Total thickness	6630 µm		

Adhesion to Values

• Steel (after 14 days)	2.3 N/cm
-------------------------	----------

Additional Information

- Density (ASTM D3574): 248 kg/m³
- Shore A Hardness (ASTM D2240): 31
- Compression Deflection @10%: 99 kPa
- Tensile Strength (ASTM D3574): 1103 kPa
- Elongation (ASTM D3574): 105%
- Thermal Conductivity (ASTM): 0.39 (BTU·in/h·ft²·°F)
- Available Widths: 6mm - 1372mm



tesa[®] 60057 Spacer Tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=60057>