



tesa® 50128 PV0

Product Information

Thick PET fleece tape for cable mounting in automotive interiors



Product Description

tesa® 50118 is a thick PET fleece tape with a new designed acrylic adhesive for applications in automotive interiors.

Features:

- excellent damping properties
- good peel resistance
- suitable for common irregular, rough and critical interior surfaces
- often suitable without any kind of surface pretreatments
- tear resistant
- can be used with automatic tape dispensers

Application Fields

Cable mounting

For quick and secure fixation of flat and round cables with excellent damping properties

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Type of liner	glassine	• Thickness of liner	70 µm
• Color	black	• Thickness of tape	390 µm
• Color of liner	white	• Weight of liner	80 g/m ²

Properties/Performance Values

• Elongation at break	100 %	• Static shear resistance	very good
• Tensile strength	33 N/cm	• Suitable for rough surfaces	very good
• Hand tearability	low	• Tack	very good
• Low VOC	very good	• Temperature resistance short term	160 °C

Additional Information

*Kiss-cut solutions or die-cuts are available under tesa® 54118

tesa's automation and application department provides customized equipment and self-designed application tools to enhance productivity.

Adhesion values to:

For latest information on this product please visit <http://l.tesa.com/?ip=50128>



tesa[®] 50128 PV0

Product Information

Additional Information

PET
PET fleece surface
PET fleece Headliner A
are not part of the product specification

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=50128>