

tesa® 07492GY

Product Information



tesa® 7492 Polyethylene Closed Cell Single Sided Foam Tape (3mm Thick / Grey)

Product Description

tesa® 7492 foam tape is a cost-effective solution for a variety of sealing applications in the concreting and general industrial settings. The foam sealing tape is resistant to temperatures from -80°C to 80°C, humidity, UV-light, solvents, plasticizers, and natural aging. The acrylic adhesive offers excellent hold on various different surfaces, even on rough exteriors. The tape's backing is comprised of a cross-linked polyethylene closed-cell foam, which is 100% watertight and therefore suitable for sealing off water and dirt. The foam tape is ideal for permanent applications on plastic. It is resistant to oil, solvents, and many chemicals, as well as fungi. The foam tape is ideal for die-cutting and is available in various different thicknesses: 3mm, 6mm, 10mm, and 12mm.

Product Features

_NULL

Application Fields

*tesa® 7492 foam tape is an ideal sealing solution for various industries such as the concreting industry*The foam tape is used for wall sealing *The tape is suitable for draft and water sealing*The foam tape can be used for sealing concrete formwork *The tape is used for sealing electrical enclosures *The foam tape is ideal for sealing between canopies and trays in recreational vehicles.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=7492GY>