

Product Information

BNR 40407

Product Description

The decorous tesa® Deluxxe towel ring offers a beautiful angular design, emphasized by the high gloss chrome finish. The ring is mounted with an adhesive technology that doesn't require drilling. Hence, surfaces don't take damage. It can be removed at any time without a trace and reused with a new adapter BK20.

Product Features

- Stable towel ring, including the tesa® Power.Kit technology (the all-in-one adhesive mounting solution)
- Modern design, angular style, high gloss chrome-plated metal, square wall plate
- Safe hold, waterproof, guaranteed stainless
- Soft close function
- Suitable for tiles, metal, natural stone, marble, concrete, wood, glass and many types of plastic
- Not suitable for wallpaper, stucco and other surfaces with non-stick coating
- Can be removed without surface damage and moved elsewhere with adapter BK20
- Effortless, clean application without drilling
- Product dimensions: 156mm x 185mm x 45mm

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|-----------------------|-------------------------|--------------------|------------|
| • Type of adhesive | Silane modified polymer | • Special features | Soft close |
| • Holding power up to | 6 Kg | | |

Properties/Performance Values

- | | | | |
|-----------------------------|---------------|-----------------------|-----------------------------|
| • Applicationfield | Bathroom | • Reusable | yes |
| • Chemical Resistance | no | • Reusable with | Adapter BK20 |
| • Curing time | 12 hour(s) | • Shape of wall piece | Rectangular |
| • Design series | tesa® DELUXXE | • Solvent free | yes |
| • Hazard material | yes | • Suitable surfaces | Glazed Tiles, Glass, Marble |
| • Material | Chromed metal | • UV resistant | yes |
| • Residue-free removability | yes | | |

tesa®

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=40407>