

tesa® 64204 Red

Product Information

Coloured Polypropylene Tape



Product Description

tesa® 64204 is a brilliantly coloured packaging tape based on a polypropylene (PP) backing with an acrylic adhesive. The PP backing gives the tape a lightness, making it easy to handle. The acrylic adhesive offers high ageing resistance as well as resistance against environmental factors such as temperature, UV light, ozone and humidity. The tape has good adhesive properties to substrates with high surface energy (polar substrates / easy to adhere surfaces). The tape is suitable for manual application and is convenient to use due to its hand-tearability. tesa® 64204 is available in numerous bright and highly visible colours such as red, yellow, blue and green. This spectrum of colours makes the tape ideal for colour-coding.

Application Fields

- Suitable for general packaging
- Used commonly for colour-coding due to the availability of bright, visible colours
- Ideal for use on recycled cardboard cartons

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing | PP film | • Total thickness | 55 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|----------------------|-----------|
| • Elongation at break | 140 % | • Hand tearability | very good |
| • Tensile strength | 34 N/cm | • Manual application | yes |

Adhesion to Values

- | | |
|---------|--------|
| • Steel | 3 N/cm |
|---------|--------|

tesa® 64204 Red

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=64204PV0RD>