

# tesa® 4302

## Product Information



High performance paper masking tape up to 160 °C

### Product Description

tesa® 4302 is a finely crêped and good conformable paper masking tape, especially suitable for the highest requirements of automotive paintworks (water- or solvent based paints) followed by oven-drying.

Paints and even critical filler systems adhere excellent to the backing avoiding any kind of flaking.

tesa® 4302 can be removed from rubber, glass and paint without tearing or leaving adhesive residues. This is specially remarkable even for cold removal after high heat cycles.

Due to its finely crêped structure, this tape guarantees sharp edged finishing.

### Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Applications

- |                    |                       |                                   |        |
|--------------------|-----------------------|-----------------------------------|--------|
| • Backing          | slightly-creped paper | • Total sustainable product excl. | 70 %   |
| • Type of adhesive | natural rubber        | liners by weight (acc. EN 16785)  |        |
|                    |                       | • Total thickness                 | 170 µm |

### Properties/Performance Values

- |                       |         |                                   |           |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 10 %    | • Hand tearability                | very good |
| • Tensile strength    | 46 N/cm | • Temperature resistance (60 min) | 160 °C    |
| • Easy to remove      | yes     |                                   |           |

### Adhesion to Values

- |         |        |
|---------|--------|
| • Steel | 4 N/cm |
|---------|--------|

# tesa® 4302

## Product Information

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=4302>