



tesa[®] 51485

Product Information



PVC Protective Tape

Product Description

Low tack adhesive, residue free removal for up to 6 months, easy unwind, low curl characteristics

Applications

- Protection of finished surfaces during fabrication
- Storage or transportation and installation. Particularly suitable for the protection of aluminium window and door frames.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|----------|-------------------|--------|
| • Backing material | PVC film | • Total thickness | 115 µm |
|--------------------|----------|-------------------|--------|

Properties/Performance Values

- | | | | |
|-----------------------|-------|--------------------|-----------|
| • Elongation at break | 200 % | • Tensile strength | 24.4 N/cm |
|-----------------------|-------|--------------------|-----------|

Adhesion to Values

- | | |
|---------|----------|
| • steel | 0.8 N/cm |
|---------|----------|



tesa[®] 51485

Product Information

Additional Information

Low tack adhesive leaves no residue on removal for up to 6 months. Highly conformable backing allows tape to mold to intricate shapes. Easy unwind and low curl characteristics for smooth operation.

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51485>