

tesa® 7250

50µm single sided solid black filmic tape

tesa® 7250 is a deep black, single sided self-adhesive tape consisting of a black PET film backing and a black tackified acrylic adhesive

tesa® 7250 features esp.

- Thickness: 50µm
- Very good light blocking performance
- High peel strength and shear resistance
- Very good repulsion resistance properties
- Very good handling performance in converting processes
- Excellent resistance to demanding environmental conditions
- Very good removability on common plastic and metallic substrates
- Pin whole free product design

Main Application

- Fixing of cables or constructive parts in LED light sources or Flat Panel displays
- Light shielding in consumer electronics parts
- Electrical insulation

Technical Data

▪ Backing material	PET film	▪ Temperature resistance short term	200 °C
▪ Total thickness	50 µm	▪ Temperature resistance long term	100 °C
▪ Type of adhesive	acrylic	▪ Dielectric breakdown voltage	4000 volt
▪ Elongation at break	50 %	▪ Transmittance (380 - 780nm) <	0.02 %
▪ Tensile strength	30 N/cm		

Adhesion to

▪ Steel (initial)	4.2 N/cm	▪ Steel (after 14 days)	5.3 N/cm
▪ ABS (initial)	3.9 N/cm	▪ ABS (after 14 days)	4.7 N/cm
▪ Aluminium (initial)	3.8 N/cm	▪ Aluminium (after 14 days)	5.3 N/cm
▪ Glass (initial)	4.3 N/cm	▪ Glass (after 14 days)	4.9 N/cm
▪ PC (initial)	3.9 N/cm	▪ PC (after 14 days)	5.2 N/cm

Properties

▪ Ageing resistance (UV)	●●●●	▪ Static shear resistance at 23°C	●●●●
▪ Humidity resistance	●●●	▪ Static shear resistance at 40°C	●●●●
▪ Softener resistance	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

For latest information on this product please visit <http://l.tesa.com/?ip=07250>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.