



tesaflex® 4169 PV8

Product Information

Floor Marking Tape Premium

Product Description

tesaflex® 4169 PV8 floor marking tape offers outstanding performance on many high-demanding floor marking applications.

tesaflex® 4169 PV8 is a tough plasticized vinyl tape, coated with an aggressive modified rubber-resin adhesive.

Equipped with a very strong and tough vinyl backing, tesaflex® 4169 PV8 features a high resistance to weak chemicals and high abrasions.

The high flexibility of tesaflex® 4169 PV8 allows application in curves without wrinkling.

Its silicon-release coated vinyl backing features a low unwinding force which offers high suitability for use with dispensers.

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Applications

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | soft PVC | • Total thickness | 203 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-------------------------------|-----------|
| • Elongation at break | 260 % | • Suitable for rough surfaces | very good |
| • Tensile strength | 45 N/cm | | |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 1.6 N/cm |
|---------|----------|

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04169>