

# tesa® 88250



## Product Information

### Low surface energy transfer tape

tesa® 88250 is a conformable, transparent, water-based acrylic transfer tape. The adhesive offers good performance on low surface energy surfaces, and has been developed for lamination and converting applications.

#### Main features:

- Available in 60" / 1524mm usable width
- Conformable to difficult 3D shapes
- Good die cutting properties

### Main Application

#### Lamination of flexible substrates

- NVH (noise, vibration, harshness) and BSR (buzz, squeak, rattle) materials
- Rubber materials for gaskets
- Plastics or vinyls for label and tag applications
- Decorative fabrics

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### Technical Data

• Backing material	none	• Color of liner	white/blue logo
• Color	transparent	• Thickness of liner	106 µm
• Total thickness	127 µm	• Weight of liner	98 g/m <sup>2</sup>
• Type of adhesive	water-based acrylic	• Temperature resistance from	-40 °C
• Type of liner	poly-coated paper		

#### Adhesion to

• Steel (after 3 days)	10.0 N/cm	• PC (after 3 days)	12.0 N/cm
• Glass (after 3 days)	11.0 N/cm	• PE (after 3 days)	5.0 N/cm

#### Properties

• Suitable for die cutting	Yes	• Static shear resistance	●
• Suitable for rough surfaces	●●●●	• Conformability	●●●●
• Tack	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

# tesa® 88250

## Product Information



### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=88250>