

# tesafilm<sup>®</sup> invisible

BNR 5540, 57095, 57312, 57333, 57335, 57414, 57477, 57484, 57485, 57552, 57649, 57652, 57660, 57661

## Product Features

- Almost invisible on light-coloured paper
- Can be written on with almost all pens
- Easy handling
- Photocopy-neutral
- High age-resistance
- Silent unwinding
- Easy and quick to remove from firm surfaces
- PP foil and solvent-free adhesive
- Suitable for use in all available tesafilm<sup>®</sup> dispensers

## Product Description

tesafilm<sup>®</sup> invisible is a self-adhesive tape for high quality crafting and paper repair. It is virtually invisible, photocopy-neutral and can be written on.

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                     |                   |       |
|--------------------|---------------------|-------------------|-------|
| • Backing material | BOPP                | • Total thickness | 52 µm |
| • Type of adhesive | water-based acrylic |                   |       |

## Properties/Performance Values

- |                          |              |                     |                  |
|--------------------------|--------------|---------------------|------------------|
| • Ageing resistance (UV) | yes          | • Suitable surfaces | Paper, Cardboard |
| • Applicationfield       | Office, Home | • Tear resistance   | no               |
| • Hand tearability       | yes          | • Tensile strength  | 20 N/cm          |
| • Low noise unwinding    | yes          | • Transparency      | medium           |
| • Photocopy neutral      | yes          | • Unwind force n/cm | 1 N/cm           |
| • Solvent free           | yes          | • Writable          | yes              |

# tesafilm<sup>®</sup> invisible

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=05540>