



Product Information



Thin paper masking tape for paint spraying

Product Description

The product is thin and flexible and, therefore, suitable for all general masking applications, as well as oven drying applications up to a temperature of 80 °C.

Sustainable Aspects



For more information: https://www.tesa.com/product-sustainability

Application Fields

- Lacquering work
- Good flexibility for curves
- Can be used on painted metal, rubber, glass and chrome parts

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

Backing materialType of adhesive	slightly-creped paper natural rubber	•	Bio-based content of liner by weight (acc. EN 16785) Total thickness	55 % 140 μm
Properties/Performance Values				
Elongation at breakTensile strengthEasy to remove	10 % 38 N/cm yes		Hand tearability Temperature resistance (60 min)	very good 80 °C
Adhesion to Values				

steel 3.3 N/cm





Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



Page 2 of 2 – as of 14/12/24 – en-GB