



tesa® 4848 PV1



Product Information

Transparent surface protection film

Product Description

tesa® 4848 surface protection film consists of a polyethylene backing which is coated with a self adhesive UV and age resistant acrylic adhesive mass.

This ensures an easy and residue free removal after up to 4 weeks.

The protection film is resistant to many chemicals and solvents, physical stress and moisture.

The transparent backing avoids a “darkroom” effect when the film is applied to windows.

Product Features

- Thin and transparent film
- UV resistance allows outdoor use for four weeks
- Sensitive adhesive with low bonding strength
- Very versatile in terms of surfaces that can be protected

Application Fields

- Indoor and outdoor applications
- For painting, plastering or facade work
- Protection of large areas against dirt and damage

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------|-------------------|-------|
| • Backing material | PE film | • Total thickness | 48 µm |
| • Type of adhesive | acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------|---------|------------------|-----|
| • Tensile strength | 12 N/cm | • Easy to remove | yes |
|--------------------|---------|------------------|-----|

Adhesion to Values

- | | |
|---------|----------|
| • steel | 0.8 N/cm |
|---------|----------|



tesa[®] 4848 PV1

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04848>