



tesa® 4370

Product Information



Cloth duct tape - 8 weeks UV resistant

Product Description

tesa® 4370 is an 8 week UV-resistant cloth tape. It consists of a PE coated 70 mesh woven PET fabric backing and a black UV-blocker, coated with a pressure sensitive natural rubber adhesive. tesa® 4370 UV extra is suitable for long term protection of delicate areas like window frames, facades, and other surfaces during plastering and painting in construction sites. Features:

- 8 weeks UV resistance
- good adhesion, even on rough surfaces
- water repellent
- conformable
- easy to remove without residues
- easy to unwind
- available in white

Application Fields

- Outdoor applications (up to 8 weeks)
- Protection of areas like window frames or facades during construction works
- Protection against dirt and damage through manufacturing tools and material
- Suitable for application on concrete/bricks, timber, glass

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|----------------|-------------------|--------|
| • Backing material | cloth | • Total thickness | 310 µm |
| • Type of adhesive | natural rubber | | |

Properties/Performance Values

- | | |
|--------------------|---------|
| • Tensile strength | 60 N/cm |
|--------------------|---------|



tesa® 4370

Product Information

Additional Information

Recommendation: please conduct a test on the application surface before using the product.

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=04370>