



# tesa<sup>®</sup> 4329 PV1



## Product Information

Finely creped paper mask tape

## Product Description

The product is thin and flexible and therefore suitable for all general masking applications, as well as oven drying applications up to a temperature of 70 °C.

## Sustainable Aspects

57% bio-based content in total product excluding liner (by weight)



## Product Features

- Good flexibility for masking of curves
- Good adhesion tack to various surfaces
- Paints and fillers adhere to the reverse side
- Temperature resistance up to 70 °C

## Application Fields

- Masking
- Lacquering work
- Good flexibility for curves
- Can be used on painted metal, rubber, glass and chrome parts

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

• Backing material	slightly-creped paper	• 57	Bio-based
• Type of adhesive	natural rubber		content of liner by
			weight (acc. EN
			16785)
		• Total thickness	125 µm

## Properties/Performance Values

• Elongation at break	10 %	• Easy to remove	yes
• Tensile strength	33 N/cm	• Hand tearability	very good

For latest information on this product please visit <http://l.tesa.com/?ip=04329>



# tesa<sup>®</sup> 4329 PV1

## Product Information

### Adhesion to Values

- steel 2.8 N/cm

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04329>