

# tesa® 4378 Easy Cover® Auto

## **Product Information**

3 in 1 - Car body masking solution for large areas

## **Product Description**

tesa® 4378 Easy Cover Auto is a convenient "3 in 1" solution for the masking of large areas for car body repair. The system includes:

- 1. Masking tape tesa® 4309
- 2. Masking paper border
- 3. HDPE masking film

The main advantage is the combination of the advantages of the single components.

- a) tesa® 4309 is a finely creped, extremely stretchable and flexible paper masking tape. It is suitable for water and solvent based paints and can be used for paint spraying with subsequent oven/ or IR-drying up to a temperature of 120 °C.
- b) The additional paper edge provides perfect paint absorption on the most critical area close to the repair.
- c) The HDPE film protects against spray particles. It is specifically treated for better paint adherence. Due to the high static the film clings to the car body.

tesa® Easy Cover Auto allows one person to cover large areas easily and quickly. For storing, transporting and disposing of tesa® Easy Cover® Auto saves space.

## **Application Fields**

- · Professional masking applications during lacquering work
- Masking of large areas before car body repair jobs
- · Protection against spray particles

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

#### **Product Construction**

Backing material slightly-creped paper
Type of adhesive natural rubber

## **Properties/Performance Values**

Elongation at break
Tensile strength
Easy to remove
Elongation at break
Material of masking coverage
Weight of addtl. protection
paper

#### Adhesion to Values

steel3.5 N/cm



# tesa® 4378 Easy Cover® Auto

**Product Information** 

# Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.