



# tesa® 64014

## Product Information



Low noise packing tape - available in clear & brown

### Product Description

tesa® 64014 is based on a PP-backing coated with a water based acrylic adhesive.

The special material combination guarantees a low noise unwind.

Due to the characteristics of the water based acrylic adhesive tesa® 64014 has a high age and light resistance. As the product is chlorine free and based on derivatives of mineral oil only, disposal by incineration is environmental friendly.

### Application Fields

- Packaging, bundling and closing
- Sealing of light and medium-range weight cartons

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |         |                   |       |
|--------------------|---------|-------------------|-------|
| • Backing material | PP film | • Total thickness | 45 µm |
| • Type of adhesive | acrylic |                   |       |

### Properties/Performance Values

- |                       |         |                      |     |
|-----------------------|---------|----------------------|-----|
| • Elongation at break | 140 %   | • Manual application | yes |
| • Tensile strength    | 35 N/cm |                      |     |

### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 2.4 N/cm |
|---------|----------|



# tesa® 64014

## Product Information

### Additional Information

tesa® 64014 can be applied by all manual dispensers. For a more convenient application it is recommended to reduce the dispenser friction. The PV1 version of the product is printable. Available colours: white, havana and transparent

### Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=64014>