

73324 TP-X

Product Information

Foam plate mounting tape: FLEX Product Design

Product Description

Double-sided foam tape

Foam properties

- · Low thickness tolerance
- · Long lasting, constant recovery characteristics

Adhesive properties

- · Medium tack surface characteristics
- · Sufficient plate bonding
- · Easy plate demounting
- · Excellent tape bonding towards sleeve side

Addtional property

- · Structured PP-liner to prevent formation of air pockets when the plate is mounted
- · Flexible PE reinforcement film to compensate for the expansion of thin-walled sleeves

Product Features

- Foam properties: Long lasting, constant recovery characteristics. Low thickness tolerance.
- Adhesive properties: Medium tack surface characteristics. Sufficient plate bonding. Easy plate demounting. Excellent tape bonding towards sleeve side.
- · Flexible PE reinforcement film to compensate for the expansion of thin-walled sleeves.

Application Fields

Mounting of 1,14 mm (0,045") and 1,70 mm (0,067") flexographic printing plates onto steel /alu /PU and glassine cylinders

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

•	Backing material	PE foam with film	•	Type of liner	PP
		lamination	•	Total thickness	550 μm

Type of adhesive tackified acrylic

Properties/Performance Values

•	Colour of foam	purple	 Thickness category 	500
---	----------------	--------	--	-----

Hardness medium



73324 TP-X

Product Information

Additional Information

Available liner options:

- PV0: White embossed PP-liner
- PV21: Transparent structured easy application (EA) PET liner for excellent air removal during plate and tape mounting

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

