



# tesa® 4204 PV5

## Product Information

Transparent packaging tape

### Product Description

The properties of the adhesive enable a good tack on all kind of surfaces and a secure seal.

The ageing stability allows long storage times for the sealed boxes, as well as superior outdoor performance. tesa® 4204 PV5 can be used on all common desk dispensers.

Compared to most other PP waterbased acrylic tapes tesa® 4204 PV 5 has an improved adhesive anchorage, which reduces the risk of adhesive residues after removal.

As the product is chlorine free and based on derivatives of mineral oil only, disposal by heat treatment is environmental friendly.

The process of cardboard waste recycling will be not affected as confirmed by leading recycling companies and paper mills.

### Product Features

- The ageing stability allows long storage times for the sealed boxes, as well as superior outdoor behaviour.
- Compared to most other PP waterbased acrylic tapes tesa® 4204 PV 5 has an improved adhesive anchorage, which reduces the risk of adhesive residues after removal.
- As the product is chlorine free and based on derivatives of mineral oil only, the disposal by heat treatment is environmental friendly.
- The process of cardboard waste recycling will be not disrupted as confirmed by leading recycling companies and paper mills.

### Application Fields

tesa® 4204 PV5 is recommended as a sealing tape for small boxes, bags, tins and drums or for fixing sheets of plastic.

### Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

### Product Construction

- |                    |         |                   |       |
|--------------------|---------|-------------------|-------|
| • Backing material | PP film | • Total thickness | 52 µm |
| • Type of adhesive | acrylic |                   |       |

### Properties/Performance Values

- |                       |       |                    |         |
|-----------------------|-------|--------------------|---------|
| • Elongation at break | 150 % | • Tensile strength | 50 N/cm |
|-----------------------|-------|--------------------|---------|

### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 3.2 N/cm |
|---------|----------|

For latest information on this product please visit <http://l.tesa.com/?ip=04204>



# tesa<sup>®</sup> 4204 PV5

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04204>