



tesa® 64624

Product Information



Double-sided filmic tape

Product Description

tesa® 64624 is a transparent double-sided filmic tape based on a PP backing and a well-balanced synthetic rubber adhesive.

tesa® 64624 has been designed to meet the requirements of trim and profile producers:

- Good unwinding properties
- Low risk of product tearing due to filmic backing
- No adhesive oozing during the transport of the trims
- Paper liner to withstand fast liner removal without tearing
- Well balanced adhesive offers high immediate adhesion, very good shear strength and sufficient tack at room temperature

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

• Backing material	PP film	• Colour	transparent
• Type of adhesive	synthetic rubber	• Colour of liner	brown
• Type of liner	glassine	• Thickness of liner	76 µm
• Total thickness	175 µm	• Weight of liner	90 g/m ²

Properties/Performance Values

• Elongation at break	140 %	• Humidity resistance	medium
• Tensile strength	45 N/cm	• Static shear resistance at 40°C	low
• Ageing resistance (UV)	low	• Tack	low

Adhesion to Values

• PC (initial)	13 N/cm	• PVC (initial)	13 N/cm
• PE (initial)	10 N/cm	• Steel (initial)	12 N/cm
• PP (initial)	8 N/cm		

Additional Information

Liner variants:

PV 00 Brown glassine liner

PV 01 White glassine liner (84µm/102gr)

PV 06 Red MOPP filmic liner (80µm/71gr)

For latest information on this product please visit <http://l.tesa.com/?ip=64624>



tesa[®] 64624

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.

For latest information on this product please visit <http://l.tesa.com/?ip=64624>