




tesa® EasySplice 51680 Rotogravure Plus



Product Information

Multifunctional splicing tape for flying splice

Product Description

tesa EasySplice® 51680 Rotogravure Plus is a double-sided integrated flying splice tape consisting of a flat-back paper and a modified acrylic adhesive.

tesa EasySplice® 51680 Rotogravure Plus features

- Highest tack properties
- Climate-resistant contact adhesive
- High shear and heat resistance
- Best adhesion values on coated and uncoated paper
- Low splice thickness
- Printable and coatable backing
- Smooth and easy application due to flexible backing

The innovative tape composition provides following functions:

- Split liner for the secure fixation of the top sheet
- Adhesive formulation with very high tack properties for excellent contact between expiring web and new reel
- One splitting strip with paper backing for a smooth opening of the new paper reel without jeopardising the printing process.

Colour: Orange

Application Fields

tesa®EasySplice® 51680 Rotogravure Plus is particularly suitable for:

- Flying splices in the rotogravure printing industry
- Best performance on wide webs and belt-driven reel stands
- Lower paper qualities

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|------------|----------|--------|
| • Backing material | flat paper | • Colour | orange |
| • Total thickness | 100 µm | | |

Properties/Performance Values

- | | | | |
|-----------------------|---------|-----------------------------------|-----------|
| • Elongation at break | 6 % | • Shelf life time (packed) < 25°C | 18 months |
| • Tensile strength | 30 N/cm | | |

For latest information on this product please visit <http://l.tesa.com/?ip=51680>



tesa® EasySplice 51680 Rotogravure Plus

Product Information

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=51680>