



# tesa® 50560 PV0 Bumperfilm

## Product Information

Temporary protection for freshly painted surfaces

## Product Description

tesa® 50560 Bumperfilm is a premium grade self adhesive film that has been developed for the protection of delicate surfaces, e.g. painted bumpers.

User benefits:

- Cost saving due to reduction in rectification and final repair
- Preserves the paint finish, up to 6 months storage outdoors
- No special equipment needed ensuring simple, low cost application and removal processes
- Good adhesion to the range of paint finishes, even during transportation (tested at speeds higher than 160 km/h - 100 mph)
- Easy disposal. Both film and adhesive system are environmentally friendly

## Product Features

- Preserves the surface finish, up to 6 months' storage outdoors
- Thick material quality for high protection
- Suitable for die cutting and printing
- Cost saving due to reduction in rectification and final repair
- No special equipment needed, ensuring simple, low-cost application and removal processes
- Good adhesion to the range of paint finishes, even during transportation (tested at speeds higher than 160 km/h / 100 mph)
- Easy disposal - the product is harmless to health and environment and can be disposed to the household or recycling waste

## Application Fields

- Protection against dirt and scratches during assembly, transport and storage of painted plastic parts or / and painted metal surfaces

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                   |                   |       |
|--------------------|-------------------|-------------------|-------|
| • Backing material | polyolefinic film | • Total thickness | 75 µm |
| • Type of adhesive | PIB               |                   |       |

## Properties/Performance Values

- |                       |           |                            |     |
|-----------------------|-----------|----------------------------|-----|
| • Tensile strength    | 16 N/cm   | • Easy to remove           | yes |
| • Chemical resistance | very good | • Suitable for die cutting | yes |

For latest information on this product please visit <http://l.tesa.com/?ip=50560>



# tesa® 50560 PV0 Bumperfilm

Product Information

## Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50560>