




# tesa<sup>®</sup> 50533 Edge Securing



## Product Information

High adhesion temporary protection tape for freshly painted surfaces

## Product Description

tesa<sup>®</sup> 50533 consists of an UV-stabilised backing coated with a high adhesion EVA adhesive.

User benefits:

- Preserves the paint finish, up to 6 months storage outdoors
- Perfect adhesive to the range of the paint finish, even during transportation (tested at speeds higher than 160 km/h – 100 mph)
- Easy disposal. Both, the film and the adhesive systems are environmentally friendly

## Product Features

- Reliable paint protection during outdoor storage for up to 12 months
- Secure high adhesion during transport
- Suitable for die cutting and printing
- Thick material quality for high protection
- Easy to apply and remove
- Easy disposal – both the film and the adhesive system are environmentally friendly
- It consists of a UV-stabilized backing coated with a high adhesion EVA adhesive.

## Application Fields

- 50533 provides effectively peeling off protection for filmic systems like tesa<sup>®</sup> 50530 especially in areas of difficult geometries and prevents infiltration by dust and humidity
- tesa<sup>®</sup> 50533 is suitable for die-cutting and can be printed to be used as security, steering or marking label
- 50533 can also be used as base material for heavy duty protection pads for bumpers and door edges

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                         |                   |                   |       |
|-------------------------|-------------------|-------------------|-------|
| • Backing material Grid | polyolefinic film | • Total thickness | 96 µm |
| • Type of adhesive Grid | EVA               |                   |       |

## Properties/Performance Values

- |                       |           |                            |     |
|-----------------------|-----------|----------------------------|-----|
| • Elongation at break | 660 %     | • Easy to remove           | yes |
| • Tensile strength    | 21.5 N/cm | • Suitable for die cutting | yes |
| • Chemical resistance | very good |                            |     |

For latest information on this product please visit <http://l.tesa.com/?ip=50533>



# tesa<sup>®</sup> 50533 Edge Securing

## Product Information

### Adhesion to Values

- steel 3 N/cm

### Additional Information

tesa<sup>®</sup> 50533 Edge Securing is also available as die cut product solution as tesa<sup>®</sup> Edge Securing 54533.

## Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=50533>