



# tesa<sup>®</sup> 4713 Paper Standard



## Product Information

tesa<sup>®</sup> 4713 – CST with Paper from Responsible Sources

## Product Description

tesa<sup>®</sup> 4713 is a general-purpose packaging tape based on a fine crepe paper backing and a natural rubber adhesive. The paper backing of tesa<sup>®</sup> 4713 is made with paper from Sustainable Sources. The natural rubber adhesive system features good adhesion to multiple surfaces as well as good tack.

One step forward

This marker is our attempt to help you determine more sustainable products more easily. Read more about it:

<https://www.tesa.com/product-sustainability>

## Sustainable Aspects



For more information: <https://www.tesa.com/product-sustainability>

## Product Features

- The paper backing of tesa<sup>®</sup> 4713 is made with paper from sustainable sources.
- The natural rubber adhesive system features good adhesion to multiple surfaces as well as good tack.

## Application Fields

- Sealing of cardboard boxes
- Suitable for light-weight packaging
- Good adhesion in recycled cardboard boxes
- Brand showcase and advertisement purposes
- Suitable for manual and automatic dispensers
- Recycling-friendly tape according to INGEDE Method

## Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

## Product Construction

- |                    |                |                   |        |
|--------------------|----------------|-------------------|--------|
| • Backing material | Paper          | • Total thickness | 125 µm |
| • Type of adhesive | natural rubber |                   |        |

## Product Assortment

- Available colors: white

For latest information on this product please visit <http://l.tesa.com/?ip=04713>



# tesa<sup>®</sup> 4713

## Paper Standard

### Product Information

#### Properties/Performance Values

- |                         |         |                      |           |
|-------------------------|---------|----------------------|-----------|
| • Elongation at break   | 8 %     | • Hand tearability   | very good |
| • Tensile strength      | 30 N/cm | • Manual application | yes       |
| • Automatic application | yes     |                      |           |

#### Adhesion to Values

- |         |          |
|---------|----------|
| • steel | 2.8 N/cm |
|---------|----------|

#### Additional Information

tesa<sup>®</sup> 4713 is available in chamois (brown) and white.

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?ip=04713>